

S K Y W A L K P O I S O N 3 X L

Type designation	Skywalk Poison3 XL
Type test reference no	DHV GS-01-1935-11
Holder of certification	Skywalk GmbH & Co. KG
Manufacturer	Skywalk GmbH & Co. KG
Classification	C
Winch towing	Yes
Number of seats min / max	1 / 1
Accelerator	Yes
Trimmers	No

B E H A V I O U R A T B E N A W E D O R T A I
F L I G H T (1 1 0 K G) I N F L I G H T (1

Test pilots



Harry Buntz



Reiner Brunn

Inflation/take-off	A	A
Rising behaviour	Smooth, easy and constant rising	Smooth, easy and constant rising
Special take off technique required	No	No
Landing	A	A
Special landing technique required	No	No
Speeds in straight flight	A	A
Trim speed more than 30 km/h	Yes	Yes
Speed range using the controls larger than 10 km/h	Yes	Yes
Minimum speed	Less than 25 km/h	Less than 25 km/h
Control movement	C	C
Symmetric control pressure	Increasing	Approximately constant
Symmetric control travel	50 cm to 65 cm	50 cm to 65 cm
Pitch stability exiting accelerated flight	A	A
Dive forward angle on exit	Dive forward less than 30°	Dive forward less than 30°
Collapse occurs	No	No
Pitch stability operating controls during accelerated flight	A	A
Collapse occurs	No	No
Roll stability and damping	A	A
Oscillations	Reducing	Reducing
Stability in gentle spirals	A	A
Tendency to return to straight flight	Spontaneous exit	Spontaneous exit
Behaviour in a steeply banked turn ⚠	A	B
Sink rate after two turns	12 m/s to 14 m/s	More than 14 m/s
Symmetric front collapse	C	C
Entry	Rocking back greater than 45°	Rocking back greater than 45°
Recovery	Spontaneous in 3 s to 5 s	Spontaneous in 3 s to 5 s
Dive forward angle on exit	Dive forward 30° to 60°	Dive forward 30° to 60°
Change of course	Entering a turn of less than 90°	Entering a turn of less than 90°
Cascade occurs	No	No
Symmetric front collapse in accelerated flight	C	C
Entry	Rocking back greater than 45°	Rocking back greater than 45°

Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 30° to 60°	Dive forward 30° to 60°
Change of course	Entering a turn of less than 90°	Entering a turn of less than 90°
Cascade occurs	No	No
Exiting deep stall (parachutal stall)		
Deep stall achieved	Yes	Yes
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Change of course	Changing course less than 45°	Changing course less than 45°
Cascade occurs	No	No
High angle of attack recovery		
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Cascade occurs	No	No
Recovery from a developed full stall		
Dive forward angle on exit	Dive forward 30° to 60°	Dive forward 30° to 60°
Collapse	No collapse	No collapse
Cascade occurs (other than collapses)	No	No
Rocking back	Less than 45°	Less than 45°
Line tension	Most lines tight	Most lines tight
Asymmetric collapse 45-50%		
Change of course until re-inflation	90° to 180°	90° to 180°
Maximum dive forward or roll angle	Dive or roll angle 45° to 60°	Dive or roll angle 45° to 60°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	Yes, no turn reversal	Yes, no turn reversal
Twist occurs	No	No
Cascade occurs	No	No
Asymmetric collapse 70-75%		
Change of course until re-inflation	90° to 180°	180° to 360°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	Yes, no turn reversal	Yes, no turn reversal
Twist occurs	No	No
Cascade occurs	No	No
Asymmetric collapse 45-50% in accelerated flight		
Change of course until re-inflation	90° to 180°	180° to 360°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	Yes, no turn reversal	No
Twist occurs	No	No
Cascade occurs	No	No
Asymmetric collapse 70-75% in accelerated flight		
Change of course until re-inflation	90° to 180°	180° to 360°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	Yes, no turn reversal	Yes, no turn reversal
Twist occurs	No	No
Cascade occurs	No	No
Directional control with a maintained asymmetric collapse		
Able to keep course	Yes	Yes
180° turn away from the collapsed side possible in 10 s	Yes	Yes
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	More than 50 % of the symmetric control travel
Trim speed spin tendency		
Spin occurs	No	No
Low speed spin tendency		
Spin occurs	No	No
Recovery from a developed spin		
Spin rotation angle after release	Stops spinning in less than 90°	Stops spinning in less than 90°

Cascade occurs No		No
B-line stall		
Change of course before release	Changing course less than 45°	Changing course less than 45°
Behaviour before release	Remains stable with straight span	Remains stable with straight span
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Cascade occurs	No	No
Big ears		
Entry procedure	Standard technique	Standard technique
Behaviour during big ears	Unstable flight	Unstable flight
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Big ears in accelerated flight		
Entry procedure	Standard technique	Standard technique
Behaviour during big ears	Unstable flight	Unstable flight
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Stable flight
Behaviour exiting a steep spiral		
Tendency to return to straight flight	Spontaneous exit	Spontaneous exit
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	Less than 720°, spontaneous recovery
Sink rate when evaluating spiral stability [m/s]	14	14
Alternative means of directional control		
180° turn achievable in 20 s	Yes	Yes
Stall or spin occurs	No	No
Any other flight procedure and/or configuration described in the user's manual		
No other flight procedure or configuration described in the user's manual		